

Rajdhani Cable Single Core unsheathed flexible bright Electrolytic annealed multi strand bare copper conductor, PVC Insulated Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694: 2010

Size (Sq.mm)	Configuration	Rate Per 90 Mtr FR PVC INSULATION	Rate Per 180 Mtr FR PVC INSULATION	Rate Per 180 Mtr FRLSH PVC INSULATION
0.50	16/0.2	861	1640	1740
0.75	24/0.2	1228	2340	2360
1.0	14/0.3	1606	3060	3120
1.5	30/0.25	2341	4460	4540
2.5	50/0.25	3885	7400	7520
4.0	56/0.3	5964	11360	11760
6.0	84/0.3	8767	16700	17300
10.0	140/0.3	14580	-	-
16.0	224/0.3	22320	-	-
		Rate Per 100 meter		
25.0	196/0.4	39200	-	-
35.0	276/0.4	54800	-	-
50.0	396/0.4	81000	-	-
70.0	360/0.5	116000	-	-
95.0	475/0.5	152000	-	-
120.0	608/0.5	194000	-	-
150.0	750/0.5	239000	-	-
185.0	925/0.5	295000	-	-
240.0	1221/0.5	387000	-	-
300.0	1527/0.5	481000	-	-

Terms & Conditions.

Prices are in Indian Rupee. (Taxes extra)

- I. Disputes, if any are subject to Kolkata Jurisdiction only.
- II. The Price List supersedes all our previous Price Lists.
- III. Prices are subject to change without prior notice.
- IV. Goods are despatched by us on Purchasers risk.

